KELLEY



• 1 HP Power Unit - 115v/1ph/60hz with 115 Volt Controls x 10' of Hose


- Power Unit with UL Approved Electrical Panel
- Push Button Control NEMA 4X with 10' of Cable
- Self Lubricating Bushings with Hardened Chrome Pins for Pivot Points
- Velocity Fuses on Cylinders to Prevent Uncontrolled Descent
- Up Travel Limit Switch
- Maintenance Blocks

Available Options

- ☐ Foot Switch with Cover NEMA 1
- ☐ In Motor Warning Beeper and Flashing
 Light on a Post X 60" High or Wall Mounted
 Bracket
- ☐ Increased Horsepower Available
- ☐ Stainless Steel
- ☐ Other____

Project Information

ob Name_			
Address			
General Contractor			
Distributor			
Model	Quantity	Voltage/Phase	



S

KELLEY

Deck Raise Standard Overall Lowered Deck Raised Ship Lower Platform Weight Model Travel Capacity Dimension Height Height Time No. [in] [lb] [in] [in] [in] [in] [sec] [lb] KZL30-2 2,000 50 x 48 72 x 54 0.50 30.50 30 1,380 30 KZL40-4 4,000 50 x 48 72 x 54 0.50 30.50 52 1,650 KZL40-2 2,000 50 x 60 72 x 66 0.50 40.50 37 1,620 40 40.50 KZL40-4 4,000 50 x 60 72 x 66 0.50 60 1,800

1612 Hutton Drive, Suite 140 ▼ Carrollton, TX 75006, USA ▼ Tel: 800-558-6960 ▼ Fax: 972-389-4766 ▼ Email: sales@kelleycompany.com ▼ www.kelleycompany.com A continuing research program is in effect at Kelley. We reserve the right to incorporate product improvement at any time without prior notice.