## Car Lifts

We offer two ranges and three standard sizes of car lifts as well as customised solutions. The standard or custom build lift is further enhanced by our wide selection of doors, finishes and controls to deliver a best-in-class experience. See our brochure for available options. Our experts will work closely with you to help you choose the best system to fit your exact needs. LX series - fully enclosed, Lift Directive 2014/33/EU compliant

**S series** - a range of man-riding semi-enclosed lifts, Machinery Directive 2006/42/EC compliant

	Range of Car Lifts – Standard sizes and capacities		
SERAPID	CL-2.5	CL-3.5	CL-5.0
Payload (t)	2,500	3,500	5,000
Car			
Max. Area (m²)*	11.3	12,6	18,6
Width (mm)– CW**	2,300	2,300	2,900
Depth (mm) – CD**	5,000	5,500	6,400
Height (mm) – CH	2,200	2,400	2,700
Doors			
Clear opening width (mm)– DW	2,100	2,200	2,700
Clear opening height (mm) – DH	2,100	2,100	2,500
Shaft			
Width (mm) – SW	3,300	3,400	4,000
Depth (mm) – SD	5,600	6,100	7,000
Pit Depth			
2006/42/EC (mm)	900	900	900
EN 81–20 (mm)	NOT AVAILABLE	1,300	1,300
Headroom above Car Height			
2006/42/EC (mm)	600	600	600
EN 81-20 (mm)	NOT AVAILABLE	1,300	1,300

\* Maximum area as defined by EN81-20 Table 7 / \*\* Custom combinations of depth and height are available up to specified maximum area. Note: All dimensions are average values and will vary according to options selected.

